

# HPD8-7

## 2.4 M | 8 FT HIGH PERFORMANCE PARABOLIC REFLECTOR ANTENNA, DUAL-POLARIZED, 7.125-7.75GHZ

The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust pole-mounts ensure “set and forget” installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it's rugged, it must be RadioWaves!



### FEATURES AND BENEFITS

- High Performance ETSI Class 2/3\* Parabolic Antennas – Excellent performance for a wide range of applications
- Fully Preassembled at the Factory – Simplifies installation on site and guarantees “factory-tested” quality
- Warranty – Industry leading 7-year warranty

\*ETSI Class depends on frequency band

### SPECIFICATIONS

#### General

Antenna Type	High Performance Parabolic Reflector Antenna	Standard RF Connector Type	CPR112G
Size, nominal	8 ft   2.4 m	Standard RF Connector Suffix	RS (append suffix to model number)
Polarization	Dual		

#### Electrical

Operating Frequency Band	7.125 - 7.75 GHz	Gain, Low Frequency	42.2 dBi
Half Power Beamwidth, Horizontal	1.1 degrees	Gain, Mid Frequency	42.6 dBi
Half Power Beamwidth, Vertical	1.1 degrees	Gain, High Frequency	42.9 dBi
Cross-Polarization Discrimination	30 dB	VSWR	1.37:1
Front to Back Ratio (F/B)	68 dB	Return Loss	-16.1 dB

## Mechanical

Fine Azimuth Adjustment	+/- 5 degrees
Fine Elevation Adjustment	+/- 5 degrees
Mounting Pipe Diameter, Min	4.5 inch   11.4 cm
Mounting Pipe Diameter, Max	4.5 inch   11.4 cm
Net Weight	424 lbs   194.5 kg
Wind Velocity Operational	90 mph   145 km/h
Wind Velocity Survival Rating	125 mph   201 km/h

Mechanical Configuration	HP8
Axial Force (FA)	2773 lbs   12334 N
Side Force (FS)	1422 lbs   6325 N
Twisting Moment (MT)	4400 ft-lbs   5965 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	5

## Regulatory Compliance

FCC	undeclared
Industry Canada Compliance	SRSP307.1 A

ETSI	302217 R1 C3
RoHS-compliant	Yes

## Shipping Information

Package Type	Wood Crate
Gross Weight	1122 lbs   508.9 kg

Dimensions, L x W x H	105 x 63 x 95in   249 x 203 x 218 cm
Shipping Volume	363.67 cu ft   10.3 cu m

\*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

## TECHNICAL DRAWINGS

