

HGSN10H1590

90 DEGREE, 15 DBI SECTOR ANTENNA, HORIZONTAL-POLARIZED, 10.15-10.65GHZ



SPECIFICATIONS

General

Antenna Type	Sector Antenna	Standard RF Connector Type	CPR90G
Size, nominal	1 ft 0.3 m	Standard RF Connector Suffix	Not Applicable: No model number suffix required
Polarization	Horizontal		

Electrical

Operating Frequency Band	10.15 - 10.65 GHz	Gain, Low Frequency	15 dBi
Half Power Beamwidth, Horizontal	90 degrees	Gain, Mid Frequency	15.2 dBi
Half Power Beamwidth, Vertical	10 degrees	Gain, High Frequency	15.4 dBi
Cross-Polarization Discrimination	30 dB	VSWR	1.5:1
Front to Back Ratio (F/B)	36 dB	Return Loss	-14 dB

Mechanical

Fine Azimuth Adjustment	+/- 10 degrees	Mechanical Configuration	SEC5
Fine Elevation Adjustment	+/- 30 degrees	Axial Force (FA)	36 lbs 160 N
Mounting Pipe Diameter, Min	2 inch 5.08 cm	Side Force (FS)	40 lbs 178 N
Mounting Pipe Diameter, Max	4.5 inch 11.4 cm	Twisting Moment (MT)	35 ft-lbs 47 Nm
Net Weight	17 lbs 7.7 kg	Operating Temperature Range	-40 to +60 C
Wind Velocity Operational	90 mph 145 km/h	Max Pressure, PSIG, (if waveguide interface)	na
Wind Velocity Survival Rating	125 mph 201 km/h		

Regulatory Compliance

FCC	undeclared
Industry Canada Compliance	undeclared

ETSI	302 326-3 SS3
RoHS-compliant	Yes

Shipping Information

Package Type	Cardboard
Gross Weight	23 lbs 10.4 kg

Dimensions, L x W x H	26 x 17 x 11in 66 x 43.2 x 27.9 cm
Shipping Volume	2.8 cu ft 0.08 cu m

*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.