

SHPD8-5.9

2.4 M | 8 FT SUPER HIGH PERFORMANCE PARABOLIC REFLECTOR ANTENNA, DUAL-POLARIZED, 5.925-6.425GHZ

The SHP Ultra High Performance Series by RadioWaves offers ultra high performance parabolic antennas engineered to provide ETSI class 3 radiation pattern performance, with exceptional front/back ration as well as excellent gain. SHP Parabolics include high performance radomes. RadioWaves field-proven antennas and robust pole-mounts ensure “set and forget” installation with minimal post-installation maintenance. If it’s rugged, it must be RadioWaves!



FEATURES AND BENEFITS

- High Performance ETSI Class 3 Parabolic Antennas with exceptional front/back ratio – Excellent performance for a wide range of applications
- Simple Assembly – Minimal required assembly simplifies installation on site and guarantees “factory-tested” quality
- Warranty – Industry leading 7-year warranty

SPECIFICATIONS

General

Antenna Type	Super High Performance Parabolic Reflector Antenna	Standard RF Connector Type	CPR137G
Size, nominal	8 ft 2.4 m	Standard RF Connector Suffix	RS (append suffix to model number)
Polarization	Dual		

Electrical

Operating Frequency Band	5.925 - 6.425 GHz	Gain, Low Frequency	41.2 dBi
Half Power Beamwidth, Horizontal	1.5 degrees	Gain, Mid Frequency	41.5 dBi
Half Power Beamwidth, Vertical	1.5 degrees	Gain, High Frequency	41.9 dBi
Cross-Polarization Discrimination	30 dB	VSWR	1.22:1
Front to Back Ratio (F/B)	76 dB	Return Loss	-20 dB

Mechanical

Fine Azimuth Adjustment	+/- 5 degrees
Fine Elevation Adjustment	+/- 5 degrees
Mounting Pipe Diameter, Min	4.5 inch 11.4 cm
Mounting Pipe Diameter, Max	4.5 inch 11.4 cm
Net Weight	424 lbs 194.5 kg
Wind Velocity Operational	90 mph 145 km/h
Wind Velocity Survival Rating	125 mph 201 km/h

Mechanical Configuration	SHP8
Axial Force (FA)	2773 lbs 12334 N
Side Force (FS)	1422 lbs 6325 N
Twisting Moment (MT)	4400 ft-lbs 5965 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	5

Regulatory Compliance

FCC	Part 101 Cat. A
Industry Canada Compliance	SRSP305.9 A

ETSI	302217 R1 C3
RoHS-compliant	Yes

Shipping Information

Package Type	Wood Crate
Gross Weight	1122 lbs 508.9 kg

Dimensions, L x W x H	105 x 63 x 95in 249 x 203 x 218 cm
Shipping Volume	363.7 cu ft 10.3 cu m

*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

TECHNICAL DRAWINGS

