

# THE LEADER IN MICROWAVE ANTENNA INNOVATION

0.6 m | 2 ft High Performance Parabolic Reflector Antenna, Dual-polarized, 2.4-2.7GHz

### HPD2-2.4



The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust polemounts ensure "set and forget" installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it's rugged, it must be RadioWaves!

### **FEATURES AND BENEFITS**

O High Performance ETSI Class 2/3\* Parabolic Antennas – Excellent performance for a wide range of applications O Fully Preassembled at the Factory – Simplifies installation on site and guarantees "factory-tested" quality

\*ETSI Class depends on frequency band

### **SPECIFICATIONS**

## General

Antenna Type	High Performance Parabolic Reflector Antenna
Size, nominal	2 ft   0.6 m
Polarization	Dual

Standard RF Connector Type	N-Female
Standard RF Connector Suffix	NS (append suffix to model number)

### **Electrical**

Operating Frequency Band	2.3 - 2.7 GHz
Half Power Beamwidth, Horizontal	14 degrees
Half Power Beamwidth, Vertical	14 degrees
Cross-Polarization Discrimination	28 dB
Front to Back Ratio (F/B)	34 dB

Gain, Low Frequency	20.4 dBi
Gain, Mid Frequency	20.9 dBi
Gain, High Frequency	21.4 dBi
VSWR	1.5:1
Return Loss	-14 dB



# THE LEADER IN MICROWAVE ANTENNA INNOVATION

## **Mechanical**

Fine Azimuth Adjustment	+/- 10 degrees
Fine Elevation Adjustment	+/- 30 degrees
Mounting Pipe Diameter, Min	2 inch   5.08 cm
Mounting Pipe Diameter, Max	4.5 inch   11.4 cm
Net Weight	27 lbs   12.3 kg
Wind Velocity Operational	90 mph   145 km/h
Wind Velocity Survival Rating	125 mph   201 km/h

Mechanical Configuration	HP2
Axial Force (FA)	202 lbs   899 N
Side Force (FS)	100 lbs   445 N
Twisting Moment (MT)	194 ft-lbs   263 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	na

# **Regulatory Compliance**

FCC	undeclared
Industry Canada Compliance	undeclared

ETSI	undeclared
RoHS-compliant	Yes

# **Shipping Information**

Package Type	Cardboard
Gross Weight	48 lbs   28.7 kg

Dimensions, L x W x H	31 x 31 x 25in   79 x 79 x 64 cm
Shipping Volume	13.9 cu ft   0.39 cu m

<sup>\*</sup>Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.



## **TECHNICAL DRAWINGS**

